

DC2i

Document Camera

**Mechanical rotation -90° / 0° / 90°
support display with various dimensions**

- HDMI Interface with Full High Definition Video Output
- 136X total zoom (17X Optical , 8X Digital)
- Presentation Aids: Various Image Effects/Remote Control
- "Pose-able" Design enables easy operation
- 8M Sensor Provides Incredible Image Quality



Model Name	DC2i	
Optical System	Lens	33-330mm / F3.4-3.8
	Working Surface	A3 (420mmx297mm)
	Zoom	17X optical zoom ;(10X zoom lens+1.7X extension zoom) ; 8X digital zoom
	Focus	Auto
Illumination System	Upper	LED Illumination System (3-stage brightness control)
	Image Sensor	1/3.2" CMOS Sensor
Image / Video	Number of Effective Pixels	8 Mega Pixels
	Still Image Resolution	8MP / 5MP / 2MP / 0.8PM
	HDMI Output Resolution	1920x1080; 1280x720
	RGB Output Resolution	1600x1200; 1024x768
	White Balance	Auto
Presentation Tools	Brightness	±7 Compensation
	Image Control	Freeze / Highlight / Mask / Flip / PIP / Slideshow
	Image Effect	Text / Graphics / B&W / Negative / Sketch
	Remote Control	Yes(IR Remote Control)
	Mechanical Arm	Yes
IO Connectors	PC Camera	Yes
	RGB Output	Yes(15-pin D-sub x1)
	RGB Input	Yes(15-pin D-sub x1)
	HDMI Output	Yes(19-pin HDMI 1.3 x1)
	HDMI Input	Yes(19-pin HDMI 1.3 x1)
External Storage	USB	Yes(USB2.0, Type B x1)
	DC 5V Input	Yes(Power Jack x1)
	SDHC Card Slot	Yes(support up to 32GB SDHC cards)
Power	Power Source	DC 5V, 100-240V, 50-60Hz
	Power Consumption	TBD
Package Content	AC/DC Adapter x1,15-pin D-sub Cable x1(Optional),USB Cable x1,HDMI Cable x1, Battery x2,Remote Control x1,Microscope Adapter x1,Anti-glare Sheet x1, Quick Guide x1,CD x1	

*Note :The specification might be modified according to company product plan without notice.

TekSpring Enterprise LTD.

• Tel: +886 3 5788558 • Fax: +886 3 5788738 • Email: sales@tekspring.com
• Address: Room 107, 1F, No. 47, Yuanqu 2nd Rd., Science Park, HsinChu 300, Taiwan